

Getac

Video Solutions



ZeroDark™ HD Camera

You work at night and so does the ZeroDark HD camera. Using a sensor designed to far surpass existing products in both quality and low-light video recording, ZeroDark excels at recording the details you need—even in darkness. The new smaller size and the ability to combine two cameras for a complete 180° view ensures you don't miss a thing.



Powerful DVR

Powerful and compact, our DVR captures video from multiple cameras and comes standard with the critical features you rely on such as on-board crash sensor, built-in battery backup, Wi-Fi, GPS and an intelligent power supply to prevent battery drain on the vehicle.



Body-Worn Camera

The Body-Worn Camera delivers panoramic, full HD video, even in low-light conditions. With one of the smallest and lightest designs in the industry, more than 12 hours of full-shift battery life and a wide range of communication features, it can go wherever the action is, providing complete situational awareness in critical scenarios.



Rugged & Fault Tolerant

Capturing the video data you need even under the most extreme conditions is necessary and can't be interrupted. You need a system that is as rugged as your team is, even when your vehicle or its power system becomes damaged. The Getac Video Solutions devices are rated Extremely Rugged and IP67 compliant.



Software Command & Control

Getac Enterprise software is one of the most powerful back-end video management tools in the industry. The highly scalable software provides dashboard overview, media management and remote management of all your systems.



Manage Data Effectively

With Getac Cloud, you can securely manage the digital assets obtained from in-car cameras, body-worn cameras, interview rooms and other digital devices. Any digital video, image or document may be securely uploaded, browsed, viewed, classified and shared using only a web browser.



ZeroDark™ HD Camera

Field-of-View: 56°(H) x 30°(V) / 125°(H) x 70°(V)
Aperture: F1.2 / F1.8
Focal Length: 6mm / 2.6mm
Low-light Capability: 0.04lux @ F1.2 (Color) / 0.05lux @ F1.8 (Color)
Exposure: Dual Exposure, HDR technology
Resolutions: 1920x1080 (1080P), 1280x720 (720P), 848x480 (D1)
Frames Per Second: 30
Dimensions: 1.77" x 1.77" x 1.97", 45mm x 45mm x 50mm (L x H x D) / 1.77" x 1.77" x 1.38", 45mm x 45mm x 35mm (L x H x D)
Weight: 0.44 lbs (200g) / 0.40 lbs (180g)

ZeroDark™ HD Infrared Backseat Camera

Field of View: 125°(H) x 70°(V)
Aperture: F1.8
Focal Length: 2.6mm
Low-light Capability: 0.00lux (IR LED On), IR: Built-In IR LEDs (4ea)
Exposure: Dual Exposure, HDR technology
Resolutions: 1920x1080 (1080P), 1280x720 (720P), 848x480 (D1)
Frames Per Second: 30
Dimensions: 1.77" x 1.77" x 1.38", 45mm x 45mm x 35mm (L x H x D)
Weight: 0.41 lbs (184g)

DVR

Recording Storage: 128-1,024GB module (M.2 slots + front lockable USB 3.0 for user supplied flash thumb drive**)
Recording Media (Removable): USB flash drive**
GPS: Integrated (Standard)
Wi-Fi: Integrated (Standard)
Battery: 7.2V / 4,200 mAh
Crash Detection: Standard 3-axis accelerometer sensor
Input/Output Ports: USB 2.0 x2, USB 3.0 x2, Ethernet x2, GPIO input x8 and GPIO output x4 for trigger events and RS232 (9 Pin) x2 for radar interface, channels composite video input x8, audio input x4, wireless microphone x2, 3.5mm Headphone, HDMI port, Control unit port and PoE x4.
Video Transfer Methods: Wireless (802.11ac), wired (Ethernet), LTE (Optional), removable USB flash thumb drive
Dimensions: 7.17" x 2.83" x 7.1", 182mm x 72mm x 180mm (L x H x D)
Weight: 4.23 lbs (1920g)
Accessories: Standard Mounting Bracket

Display

Size: 5-inch
Type: TFT LCD HD
Resolution: 800 x 480
Touch: Multi-touch technology
Buttons: Power/covert op, menu, brightness, stop record, start record, play, zoom/volume, microphone, camera
Ports: USB 2.0 (admin lockable)
Dimensions: 5.4" x 4.4" x 0.8" (L x H x D - excluding mount and projecting parts)
Weight: 0.6 lbs

Video System

Video Compression: H.264 high profile
Recording Triggers: Manual, crash and up to 8 customizable triggers
Storage Architecture: Multiple drive architecture
Pre and Post-Event: Yes, independently configured
Background Recording: Yes
Temperature Range: Operating temperature -30°C to 60°C
Temperature Range: Operating humidity 10% to 80% (no condensation)
Operating Voltages: 12/24 volts DC

Wireless Microphone

Frequency Range: 2401.056 MHz ~ 2478.816 MHz
Communication Range: 1500 ft. (in line of sight)
Talk Time: 12 Hours
Dimensions: 2.8" x 2" x 0.9"
Weight: 0.2 lbs

Body-Worn Camera

Video Output Format: .MP4 (H.264)
Video Output Resolution: 1920x1080(1080p), 1280x720(720p), 640x480(480p)
Video Output Frame Rate: 30 fps
FOV (Field of View): 120°
Storage: 64 GB
Recording Time: <12 hrs*
Stand-by Time: <24 hrs*
Watermark: Supports Date/Time/Officer ID stamp overlay on video footage
Pre-record: Supports 10; 20; 30 seconds
Addtl. Supported Features: Covert recording mode, Instant record, Instant event classification, Footage bookmarking
Buttons: Power, Main, Category Wheel, Covert Switch
I/O Interface: Docking x 1
Additional features: GPS, Wi-Fi Offload, & Built-in RFID Tag
Connectivity Interface: Wi-Fi 802.11 b/g/n, Bluetooth LE
Power: Battery 4.2V, 3220 mAh; AC Adapter/Charging Dock (5V, 2A, 10W, 100-240VAC, 50 / 60Hz)
Rugged Features: MIL-STD-810G, Vibration & 6 feet drop resistant, IP67
Environmental Spec: Operating Temp: -4°F to 122°F; Storage Temp: -40°F to 160°F
Dimensions (W x D x H): 2.98" x 2.01" x 0.93"
Weight: 4.59 oz
Attachment: Pocket mount x 1, Molle Mount x1, Chest Clip x1, Chest Mount x1, Epaulette Clip x1, Magnetic Mount x1, Magnetic Charging Cable x1

Warranty

1 year limited warranty†

Standard and optional features vary depending on purchased configuration and options selected. Specifications subject to change without notice.

* Battery performance will vary based on power management settings and environmental conditions. As with all batteries, maximum capacity decreases with time and use and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

** Flash thumb drive sold separately.

† For warranty terms and conditions visit www.getac.com

Copyright 2018, Getac, All Rights Reserved. Getac, Getac logo, and ZeroDark™ are either registered trademarks or trademarks of Getac Technology Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.